




Thomson
QXE BEARING ISOLATOR

THOMSON PERFORMANCE SEALING

Thomson QXE BEARING ISOLATOR

THOMSON PERFORMANCE SEALING


The Thomson QXE Bearing Isolator combines proven labyrinth technology with an innovative expeller design.



- Minimize Shaft Wear
- Eliminate Oil Leaks
- Prevent Contamination
- Improve Lubricant Life
- Reduce Maintenance Costs
- Optimize Bearing Life

Reliable Bearing
Protection and Extended
MTBF with Thomson
QXE Bearing Isolators

Thomson QXE Bearing Isolator




The QXE is a true, non-contact bearing isolator utilizing double vertical internal chambers. Centrifugal force adds energy to contaminants, deflecting them away from your housing while effectively retaining lubrication. Two static internal coalescing o-rings exclude vapor ingress by breaking it down and directing it to the contamination exclusion chambers. The QXE can be split for ease of installation.

- **Expels contaminants**
- **Eliminates lubrication leakage**
- **Protects against water ingress**

The QXE maximizes bearing life and significantly reduces operating costs. **SAVE ON:**

- **Lubricants**
- **Oil changes**
- **Labor and overtime**
- **Bearing replacements**
- **Equipment failures**
- **Downtime**

Thomson QXE Range:





Problem: The #1 cause of bearing failure is contaminants entering the bearing environment.

Solution: Thomson QXE.

Rotating equipment is the heart of industry and lubricating oil is the life blood. When lubricants fail, machines break down and your process grinds to a halt!

“The primary cause of bearing failure is lubricant contamination. The Thomson QXE keeps contaminants out of the bearing environment, ensuring reliable plant operation.”

The most common entry point for bearing contaminants is through a failed oil seal. The Thomson QXT bearing isolator has solved this problem in even the most demanding applications.

Clean Oil + Thomson QXE = Longer Bearing Life!

The Importance of Bearing Protection

Eliminating sources of lubricant contamination has proven to have the highest reliability impact with some of the greatest ROI.

FACT: 63% of bearing failures are due to lubrication related wear issues. Of these, 52% are due to oil contamination.


FACT: Only 10% of bearings ever reach their L10 life before failing or being replaced.

FACT: 70% of lost machine life is caused by surface degradation: 50% Mechanical wear. 82% of mechanical wear is due to particle contamination.

FACT: Mitigation of mechanical wear and corrosion are two of the primary functions of a lubricant.

Corrosion resistant materials are available upon request.


Thomson QXE - Eliminating the #1 threat to bearing life!



CAUSES OF BEARING FAILURE

Sourced from multiple studies conducted by SKF, MIT, NRCC and STLE. Data compiled from studies conducted across several industries, including pulp and paper, mining, forestry, transportation, and power generation.


Oil Contamination Rates & Oil Changes



Hybrid seal design: proven labyrinth technology + new QXE technology.

Oil Contamination Rates & Oil Changes

As contamination levels increase, oil changes are required more often.



No contamination means no oil changes, no downtime, no leakage, and no labor.

Thomson QXE – Keeping Contaminants Out and Lubrication In, Increasing MTBF by Maximizing Bearing Life.

Other Products



METALLIC GASKETS

Thomson CANFLEX® spiral wound, camprofile, high temperature, heat exchanger and ring joint gaskets. We manufacture gaskets from all common metals, exotic alloys and filler materials in all configurations for the most extreme applications.




FASTENERS

All thread studs – ASTM 193 Grade B7, B7M, B8, B8M, B16, ASTM A320 L7, L7M; heavy hex nuts – ASTM A194 Grade 2H, 2HM, 4, L7, L7M, 8 and 8M; Through hardened washers – ASTM F-436; custom coatings; specialty fabricated and machined studs; CANFLEX® approved thread lubricant.



SUPERLOK CANADA

Instrumentation Tube, Pipe, JIC and DIN Fittings. Instrumentation Ball, Bleed, Check, Double Block and Bleed, Needle, Plug, and Purge Relief Valves. Quick Connects and Filters. Flexible Metal Hose, Tubing and Accessories.



INDUSTRIAL HOSES & EXPANSION JOINTS

Hoses: Metal braided, elastomeric utility steam, air, water, nitrogen, hydrocarbon, and material handling. With CRN and CSA certifications, NAHAD guideline assemblies and mobile, on-site hose testing unit available. **Expansion Joints:** Pipeline, flue duct, metallic, rubber lined, Teflon®, Teflon® lined and splicing kits.



A.R. THOMSON GROUP

FLUID CONTAINMENT AND CONTROL SPECIALISTS SINCE 1967

The A.R. Thomson Group was established in 1967 as a regional manufacturer & distributor of gaskets and other fluid containment products. With the rapid growth of oil and gas production, petrochemical, oil refining and pulp and paper industries, our manufacturing facilities expanded to meet increased demand for these products. Since 1967, we have developed our expertise and know-how to become the leader in solving fluid containment and control problems.

No matter your control or containment needs, we can help.



To find your nearest branch, please visit ARTHOMSON.COM