GARLOCK KLOZU<mark>RE® HIGH-PERFORMANCE DYNAMIC SEALS</mark>

MICRO-TEC® II Bearing Isolator

Metallic Bearing Isolator with Micro-Cellular Filter

The Metallic Isolator with a built-in air filte<mark>r...</mark>

- Microcellular filter to block out airborne contamination
- No wear on shaft or metallic components
- Cam-Lock design means easy installation — No tools required
- Rated to IP56 Per NEMA MG 1-2003
- Surpasses IEEE 841-2001 Test Standards
- Available in a broad range of configurations
- API Compliant
- Enhanced vapor blocking capability

Design Parameters

- Temperature: -30°F (-34°C) to 400°F (204°C)
- Shaft-to-bore misalignment to ±0.020" (0.51mm)
- Axial motion to ± 0.025 " (0.64mm)
- Surface speed to 4,500 fpm (22.9 m/s)
- Fluoroelastomer mounted o-rings standard

www.microtec2.com



Microcellular Filter

GARLOCK KLOZURE® HIGH-PERFORMANCE DYNAMIC SEALS

Microcellular Filter

Only the MICRO-TEC[®] II incorporates a unique microcellular filter to block the ingress of outside contaminants. Bearing isolators with conventional labyrinth seal designs provide only limited airborne contaminant protection.

Patented Unitizing Ring

Unlike other isolators that use a simple o-ring, our patented unitizing ring completely eliminates metal-to-metal contact between the rotor and stator. Lack of axial protection can allow the bronze components to contact. Rotation and misalignment cause abrasion and shredding of the internal o-ring, leading to debris and failure.

Patented Cam-lock Design

The patented Cam-lock design of the MICRO-TEC[®] II gives it double the retaining power versus standard bearing isolator designs. This design also allows easy installation by hand, without the need for an arbor press. The interference fit of other designs require special tools for installation and may generate bronze shavings that result in bore scoring.

* Patent Pending

AUTHORIZED DISTRIBUTOR

WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Garlock. Failure to select the proper sealing products could result in property damage and/or serious personal injury.

Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing.

While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice. GARLOCK is a registered trademark for packings, seals, gaskets, and other

products of Garlock.

© Garlock Inc 2009. All rights reserved worldwide.

Garlock Klozure®

A Division of Garlock Sealing Technologies® 1666 Division Street Palmyra, New York 14522 USA 1.315.597.4811 Fax 1.315.597.3140 Toll Free 1.866.KLOZURE (1.866.556.9873) Toll Free Fax: 1.866.OILSEAL (1.866.645.7325)

Visit Klozure:

www.klozure.com www.microtec2.com



Garlock Sealing Technologies® is an EnPro Industries company.

Other Garlock brand facilities are located in:

Columbia, SC, USA	1-803-783-1880	Fax: 1-803-783-4279
Houston, TX, USA	1-281-459-7200	Fax: 1-281-458-0502
Sydney, Australia	61-2-9793-2511	Fax: 61-2-9793-2544
São Paulo, Brazil	55-11-4352-6161	Fax: 55-11-4352-8181
Sherbrooke, Canada	1-819-563-8080	Fax: 1-819-563-5620
West Yorkshire, England	44-1422-313600	Fax: 44-1422-313601
Saint-Étienne, France	33-4-7743-5100	Fax: 33-4-7743-5151
Neuss, Germany	49-2131-3490	Fax: 49-2131-349-222
Mexico City, Mexico	52-555-567-7011	Fax: 52-555-368-0418
Shanghai, China	86-021-62789702	Fax: 86-021-62787826
Singapore	65-6285-9322	Fax: 65-6284-5843
Dubai, UAE	971-4-8833652	Fax: 971-4-8833682

PRINTED IN U.S.A.

KLZ 2:78 VIA-1/09-RevB

